



TECHNICAL SHEET



Entry parking stand

DTIF, DTOF double height parking stand for issuing / checking parking tickets funfold 145g, 85.6 x 54 mm, used for entry and exit control to areas with operation of cars, trucks or buses. Basic tray capacity is 2 x 5000 tickets.

The parking stand is used for issuing / checking parking tickets, evaluating and displaying data from the subscriber's parking card and communicating with the operator. Basic information is displayed on a two-line backlit display. The stand uses also an automatic voice messaging. It controls the entry / exit automatic barrier. The stand powers the entry / exit barriers as well as protective elements. It communicates with the server via TCP/IP.



Mechanical construction:

The stand is made of 1.5 mm galvanized sheet steel, painted RAL7035 (light gray)

Dimensions: 2200 x 280 x 350

Weight: 70 kg

Line-up:

- 2 x Parking ticket printer / 2 x barcode scanner
- 2 x Subscriber Parking Card Reader (MIFARE standard)
- 2 x Two-line backlit 20-character display
- 2 x Control unit with minicomputer, Linux operating system
- 2 x I / O board
- 2 x Button
- 2 x IP audio unit
- Thermostatically controlled heating element

Extension:

- 6 "Color display
- Parking ticket printer, tray capacity 5000 tickets
- Barcode scanner
- RFID tag reader with reading distance up to 3m
- Driver camera
- LPR camera
- I / O board for connecting additional devices

Technical specification

Power supply:	230 VAC, 50Hz,
Fuse:	16A / 1B
Power input with heating:	950 VA
Protection class:	IP43 / 20
Operating temperature	-20 ° C to +50 ° C
Mounting:	on a base plate or concrete foundation

Identification media



The parking card is used to charge short-term parking and to identify subscribers. By default Mifare / Legic type is used. Different card type can also be used as a subscription card.

RFID sticker, dimensions 92 x 24 x 0,2 mm, frequency 860 - 960 MHz is used for remote identification of subscriber vehicles, reading distance is up to 5m